



PREFERRED WIRE PRODUCTS, INC.

Product Specification Sheet

'PREFERRED BRAND' 1-1/2" - 17 Gauge Galvanized Self-Furred Stucco Netting

- **Product:** 'Preferred Brand' 1.5" – 17 Gauge Galvanized Self-Furred Stucco Netting
- **Manufacturer:** Preferred Wire Products, Inc., 401 N. Minnewawa Ave., Clovis, CA 93611
- **Specifications:**
 - **Dimensions:** 150 feet Length x 36 inches Wide (50 Sq. Yds)
 - **Made with:** 17 Gauge galvanized wire
 - **Furring:** 3/8" deep *Channel Furr™* in 8 rows across the netting
 - **Conforms to:** ASTM No. A641-98 – Galvanized Wire Requirements (Class 1 galvanization)
ASTM No. C1032-98 – Woven Wire Lath Requirements
ASTM No. C1063-99 – Furring and Installing Woven Wire Base Requirements
AC 191 ICC-ES Acceptance Criteria for Metal Plaster Bases (Lath)
 - **Certified By:** ICC Report No. ESR-2055 – available upon request
 - **Complies with:** 2021 International Building Code & 2021 International Residential Code

'PREFERRED BRAND' 1" – 20 Gauge Galvanized Stucco Netting

- **Product:** 'Preferred Brand' 1 Inch – 20 Gauge Galvanized Stucco Netting
- **Manufacturer:** Preferred Wire Products, Inc., 401 N. Minnewawa Ave., Clovis, CA 93611
- **Use:** For use as specified in the ICC/ICBO Evaluation Report of the One-Coat Plaster system (by Manufacturer) used.
- **Specifications:**
 - **Length:** 150 feet Length x 37 inches minimum (51.38 Sq. Yds)
 - **Made with:** 20 Gauge galvanized wire
 - **Furring:** 11 rows of 1/8" deep furr points every 2.25" along the length of the netting
 - **Conforms to:** ASTM No. A641-98 – Galvanized Wire Requirements (Class 1 galvanization)
ASTM No. C1032-98 – Woven Wire Lath Requirements
ASTM No. C1063-99 – Furring and Installing Woven Wire Base Requirements
AC 191 ICC-ES Acceptance Criteria for Metal Plaster Bases (Lath)
 - **Certified By:** ICC Report No. ESR-2055 – available upon request
 - **Complies with:** 2021 International Building Code & 2021 International Residential Code
 -

Installation for both types of stucco netting (lath)

The stucco netting (lath) is to be installed with the long dimension perpendicular to the supports, except at the gable walls where the lath may be installed with the long dimension parallel to the roof slope.

The stucco netting (lath) is attached with appropriate fasteners; the fasteners spaced not more than seven inches on center along supports. The netting shall be overlapped by at least the dimension of its opening, ie., by at least one inch for the 1"-20 gauge netting, and by at least one-and-a-half inches for the 1.5" – 17 gauge netting.

These are general installation guidelines that may be altered according to other local, etc., building codes.